

Frequency: 50hz

Genset Model	Prime Power		Standby Power		Engine Model	Fuel Consumption (L/H)	Genset Dimension L*W*H(mm)	Weight (KG)
	KW	KVA	KW	KVA				
BC275-d	200	250	220	275	NT855-GA	53.0	2950x1100x1900	2200
BC275-e	200	250	220	275	MTA11-G2A	55.0	2830x1100x1710	2200
BC275-f	200	250	220	275	MTA11-G2	52.0	2830x1100x1710	2200
BC275-g	200	250	220	275	NTA855-G1	59.0	2950x1100x1900	2800
BC313	220	275	250	313	NTA855-G1A	61.0	2950x1100x1900	2850
BC350-a	250	313	280	350	MTAA11-G3	61.3	2980x1100x1710	2500
BC350-b	250	313	280	350	NTA855-G1B	68.0	3060x1100x1710	3000
BC350-c	250	313	280	350	NTA855-G2	68.0	3060x1100x1710	3000
BC375	275	344	300	375	NTA855-G2A	72.0	3060x1100x1710	3000
BC388	280	350	310	388	NTA855-G4	75.0	3060x1100x1710	3100
BC413	292	365	330	413	NTAA855-G7	85.0	3060x1230x2000	3150
BC450			360	450	NTAA855-G7A	98.0	3100x1230x2000	3400
BC414	292	365	330	414	KTA19-G2	83.0	3100x1310x2130	3500
BC438	320	400	350	438	QSNT-G3	70.5	3100x1310x2130	3500
BC500	360	450	400	500	KTA19-G3	97.0	3140x1310x2130	3600
BC563-a	400	500	450	563	KTA19-G3A	106.9	3250x1310x2130	4000
BC563-b	400	500	450	563	KTA19-G4	107.0	3250x1310x2130	4000
BC632	420	525	505	632	KTAA19-G5	113.0	3470x1550x2200	4100
BC650-a	460	575	520	650	KTAA19-G6	118.5	3470x1550x2200	4350
BC650-b			520	650	KTA19-G8	141.4	3270x1310x2200	4400
BC688			550	688	KTAA19-G6A	155.0	3570x1550x2200	4500
BC700	500	625	560	700	KT38-G	140.0	4050x1700x2500	6500
BC713	520	650	570	713	QSKTAA19-G4	143.0	3600x1550x2500	4700
BC788	570	712.5	630	788	KTA38-G1	160.4	4200x1700x2500	6500
BC800	580	725	640	800	KT38-GA	168.2	4200x1700x2500	6500
BC825	600	750	660	825	KTA38-G2	167.0	4200x1700x2500	6500
BC888	640	800	710	888	KTA38-G2B	167.3	4200x1700x2500	6500
BC1000	728	910	800	1000	KTA38-G2A	191.0	4300x1700x2500	7000
BC1100	800	1000	880	1100	KTA38-G5	209.0	4250x2060x2500	7200
BC1250			1000	1250	KTA38-G9	247.5	4250x2060x2520	8000
BC1375-a	1000	1250	1100	1375	QSK38-G5	274.0	4470x2080x2820	8200
BC1375-b	1000	1250	1100	1375	KTA50-G3	254.0	4830x2060x2350	8800
BC1650-a	1100	1375	1320	1650	KTA50-G8	289.0	5430x2120x2550	9600
BC1650-b	1200	1500	1320	1650	KTA50-GS8	308.8	5430x2120x2550	9600

Frequency: 60hz

Genset Model	Prime Power		Standby Power		Engine Model	Fuel Consumption (L/H)	Genset Dimension L*W*H(mm)	Weight (KG)
	KW	KVA	KW	KVA				
BC275-h			220	275	NT855-GA	53.4	2950x1100x1930	2700
BC344	250	313	275	344	NTA855-G1	73.4	2960x1100x1900	3000
BC375-a	275	344	300	375	NTA855-G1B	73.4	3060x1100x1910	3100
BC375-b	275	344	300	375	NTA855-G2	80.5	3060x1100x1910	3100
BC438	315	394	350	438	NTA855-G3	87	3060x1100x1910	3100
BC500-a	350	438	400	500	KTA19-G2	98	3100x1310x2150	4150
BC563	410	513	450	563	KTA19-G3	111	3100x1310x2150	4200
BC625-a	450	563	500	625	KTA19-G3A	102	3200x1310x2190	4250
BC625-b	450	563	500	625	KTA19-G4	122	3200x1310x2190	4300
BC688-a	470	588	550	688	KTAA19-G5	134	3470x1550x2200	4350
BC713-a	500	625	570	713	QSK19-G4	140	3600x1550x2500	4650
BC750-a	550	688	600	750	QSK19-G5	151	3600x1550x2500	4650
BC750-b			600	750	KTAA19-G6A	140	3570x1550x2200	4450
BC850	620	775	680	850	KT38-G	154	4100x1700x2500	7200
BC963	700	875	770	963	KTA38-G1	166	4200x1700x2500	7250
BC1000	725	906	800	1000	KTA38-G2	204	4200x1700x2500	7450
BC1038	750	938	830	1038	KTA38-G2B	225	4200x1700x2500	7450
BC1125	800	1000	900	1125	KTA38-G2A	225	4200x1700x2500	7450
BC1250	900	1125	1000	1250	KTA38-G4	245	4200x2060x2640	7700
BC1438	960	1200	1150	1438	QSKTA38-G5	262	4470x2000x2820	8600
BC1375			1100	1375	KTA38-G9	256	4250x2060x2600	8500
BC1563	1100	1375	1250	1563	KTA50-G3	291	4730x2000x2350	9700
BC1875	1250	1563	1500	1875	KTA50-G9	330	5480x2150x2550	10600